

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).  
 Revision Date: 02/24/2022      Date of Issue: 01/26/1995      Supersedes Date: 10/29/2019      Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Substance

**Product Name:** Safety-Kleen Premium Solvent (Virgin and Recycled)

**CAS-No.:** 64742-47-8

**Product Code:** 82658

**Synonyms:** Safety-Kleen Premium Gold Solvent; Safety-Kleen Continued Use Product Solvent (CUP); High Flash Degreasing Solvent; Parts Washer Solvent; Petroleum Distillates; Petroleum Naphtha; Naphtha, Solvent; Mineral Spirits

**SDS No.:** 82658

#### 1.2. Intended Use of the Product

Cleaning and degreasing metal parts. For professional use only.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Manufacturer

Safety-Kleen Systems, Inc.  
 42 Longwater Drive  
 Norwell, MA 02061-9149  
 1-800-669-5740

[www.safety-kleen.com](http://www.safety-kleen.com)

##### Supplier in Canada

Safety-Kleen Canada, Inc.  
 25 Regan Road  
 Brampton, Ontario L7A 1B2  
 Canada

#### 1.4. Emergency Telephone Number

**Emergency Number** : 1-800-468-1760

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Flam. Liq. 4	H227
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US/CA Labeling

**Hazard Pictograms (GHS-US/CA)** :



**Signal Word (GHS-US/CA)** :

Danger

**Hazard Statements (GHS-US/CA)** :

H227 - Combustible liquid.  
 H304 - May be fatal if swallowed and enters airways.  
 H315 - Causes skin irritation.  
 H336 - May cause drowsiness or dizziness.

**Precautionary Statements (GHS-US/CA)** :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261 - Avoid breathing vapors, mist, or spray.  
 P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P280 - Wear protective gloves, protective clothing, and eye protection.  
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
 P302+P352 - IF ON SKIN: Wash with plenty of water.  
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for



## Safety-Kleen Premium Solvent (Virgin and Recycled)

### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

breathing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

P321 - Specific treatment (see section 4 on this SDS).

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.

403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Name	Synonyms	Product Identifier	% *
Petroleum distillates, hydrotreated light	Distillates (petroleum), hydrotreated light / Distillates, petroleum, hydrotreated light / Hydrotreated light distillate / Kerosene, hydrotreated / Petroleum distillates, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 150-290°C.)	(CAS-No.) 64742-47-8	100

### 3.2. Mixture

Not applicable

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause drowsiness and dizziness. Causes skin irritation. May be fatal if swallowed and enters airways.

**Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** Repeated exposure may cause skin dryness or cracking.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

**SECTION 5: FIRE-FIGHTING MEASURES****5.1. Extinguishing Media**

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid.

**5.2. Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Combustible liquid. Will float and can be reignited on water surface.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

**5.3. Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates and gases, including carbon monoxide and unidentified organic and inorganic compounds. If sulfur compounds are present in appreciable amounts, combustion products may include also H<sub>2</sub>S and SO<sub>x</sub> (sulfur oxides) or sulfuric acid.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

**5.4. Reference to Other Sections**

Refer to Section 9 for flammability properties.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1. Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

**6.1.1. For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

**6.1.2. For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Ventilate area. Eliminate ignition sources.

**6.2. Environmental Precautions**

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

**6.3. Methods and Materials for Containment and Cleaning Up**

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

**6.4. Reference to Other Sections**

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for Safe Handling**

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray. Take precautionary measures against static discharge. Use only non-sparking tools.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

**7.2. Conditions for Safe Storage, Including Any Incompatibilities**

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

**Incompatible Materials:** Strong oxidizers.

### 7.3. Specific End Use(s)

Cleaning and degreasing metal parts. For professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Proper grounding procedures to avoid static electricity should be followed.

**Personal Protective Equipment:** Gloves. Protective clothing. Safety glasses. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Safety glasses with side shields.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, colorless to pale yellow
Odor	: Mild, hydrocarbon
Odor Threshold	: 30 ppm (based on Stoddard Solvent)
pH	: No data available
Evaporation Rate	: < 1 (butyl acetate = 1)
Melting Point	: -49 °C (-56.2 °F)
Freezing Point	: -43 °C (-45.4 °F)
Boiling Point	: 192 – 205 °C (377.6 – 401 °F)
Flash Point	: > 67 °C [Tagliabue(ASTM D-56)] (152.6 °F)
Auto-ignition Temperature	: 220 °C (428 °F)
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: 0.8 %
Upper Flammable Limit	: 6 %
Vapor Pressure	: 0.067 kPa (0.5 mmHg)[room temperature]
Relative Vapor Density at 20°C	: 5 (air = 1)
Relative Density	: No data available
Density	: ≈ 6.67 lb/gal
Specific Gravity	: 0.77 - 0.82 @ @ 16 °C (60 °F)



## Safety-Kleen Premium Solvent (Virgin and Recycled)

### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Solubility</b>	: Water: Insoluble
<b>Partition Coefficient: N-Octanol/Water</b>	: No data available
<b>Viscosity</b>	: No data available
<b>VOC content</b>	: 100 % ; 6.4 to 6.7 LB/US gal; 770 to 800 g/l; As per 40 CFR Part 51.100(s); Consult with your state/local air pollution control agency and their rules and regulations for specific direction in your specific area.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity:

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

#### 10.2. Chemical Stability:

Combustible liquid. May form flammable or explosive vapor-air mixture.

#### 10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

#### 10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

#### 10.5. Incompatible Materials:

Strong oxidizers.

#### 10.6. Hazardous Decomposition Products:

None expected under normal conditions of use.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

#### LD50 and LC50 Data:

No additional information available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** Repeated exposure may cause skin dryness or cracking.

#### 11.2. Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 2.11 mg/l/4h
Toluene (108-88-3)	

## Safety-Kleen Premium Solvent (Virgin and Recycled)

### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

LD50 Oral Rat	2600 mg/kg
LD50 Dermal Rabbit	12000 mg/kg
LC50 Inhalation Rat	25.7 mg/l/4h

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General: Not classified.

#### Safety-Kleen Premium Solvent (Virgin and Recycled) (64742-47-8)

LC50 Fish 1	> 500 mg/l
-------------	------------

### 12.2. Persistence and Degradability

#### Safety-Kleen Premium Solvent (Virgin and Recycled) (64742-47-8)

Persistence and Degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative Potential

#### Safety-Kleen Premium Solvent (Virgin and Recycled) (64742-47-8)

Bioaccumulative Potential	Not established.
---------------------------	------------------

### 12.4. Mobility in Soil

No additional information available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology - Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name	: COMBUSTIBLE LIQUID, N.O.S. (PETROLEUM DISTILLATES)
Identification Number	: NA1993
Packing Group	: III



**Special Provisions:** 49CFR173.150. Not regulated for transport in single packages less than 119 US Gal / 450 L (bulk package). Non-bulk packages are not regulated.

**14.2. In Accordance with IMDG** Not regulated for transport

**14.3. In Accordance with IATA** Not regulated for transport

**14.4. In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

#### Safety-Kleen Premium Solvent (Virgin and Recycled) (64742-47-8)

SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Skin corrosion or Irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Aspiration hazard
-------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## Safety-Kleen Premium Solvent (Virgin and Recycled)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 15.2. US State Regulations

#### California Proposition 65



**WARNING:** This product can expose you to Benzene, p-Dichlorobenzene, Ethylbenzene, Cumene, and Naphthalene, which are known to the State of California to cause cancer Benzene and Toluene which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Benzene (71-43-2)	X	X		X
Ethylbenzene (100-41-4)	X			
Naphthalene (91-20-3)	X			
Benzene, 1,4-dichloro- (106-46-7)	X			
Toluene (108-88-3)		X		
p-Dichlorobenzene (106-46-7)	X			
Cumene (98-82-8)	X			

### 15.3. Canadian Regulations

**Petroleum distillates, hydrotreated light (64742-47-8)**

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 02/24/2022

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

#### GHS Full Text Phrases:

Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness

#### NFPA Health Hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

#### NFPA Fire Hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

#### NFPA Reactivity Hazard

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



The information contained herein is correct to the best of our knowledge, information, and belief and is designed only as guidance for the handling, use, processing, storage, transportation, disposal, and release of the product. User assumes all risks incident to use of this product and shall determine the quality and suitability of the product for its use. Supplier offers no warranty, express or implied, whatsoever, including warranties of merchantability or fitness for a particular purpose or otherwise, and specifically disclaims any and all liability for incidental, consequential, or other damages arising out the use or misuse of the product. The information provided relates only to the specific material provided and may not be valid if used in combination with any other materials or process, unless specified herein.



## Safety-Kleen Premium Solvent (Virgin and Recycled)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

---

NA GHS SDS 2015 (Can, US)